NAME

rgbds - object file format documentation

DESCRIPTION

This is the description of the object files used by rgbasm(1) and rgblink(1). Please, note that the specifications may change. This toolchain is in development and new features may require adding more information to the current format, or modifying some fields, which would break compatibility with older versions.

FILE STRUCTURE

The following types are used:

LONG is a 32âbit integer stored in littleâendian format (Intel). BYTE is an 8âbit integer. STRING is a 0âterminated string of BYTE.

; Header

```
BYTEID[4]; "RGB4"LONGNumberOfSymbols; The number of symbols used in this fileLONGNumberOfSections; The number of sections used in this file
```

; Symbols

REPT	NumberOfSymbols			;	Number of symbols defined in this object file.
ST	STRING Name			The name of this symbol. Local symbols are stored as "Scope.Symbol".	
BY	BYTE TY		e	;	<pre>0 = LOCAL symbol only used in this file. 1 = IMPORT this symbol from elsewhere (unused). 2 = EXPORT this symbol to other objects.</pre>
IF	1	Type != 1		;	If symbol is defined in this object file.
	LONG	r,	SectionID		The section number (of this object file) in which this symbol is defined.
	LON	G	Value		The symbols value. It's the offset into that symbol's section.

ENDC

ENDR

```
; Sections
```

REPT NumberOfSections

STRING Name ; Name of the section

; 6 = SRAM

LONG Size ; Size in bytes of this section BYTE Type ; 0 = WRAMO ; 1 = VRAM ; 2 = ROMX ; 3 = ROMO ; 4 = HRAM ; 5 = WRAMX ; 7 = OAM

- LONG Org ; Address to fix this section at. -1 if the linker should ; decide (floating address).
- LONG Bank ; Bank to load this section into. -1 if the linker should ; decide (floating bank). This field is only valid for ROMX, ; VRAM, WRAMX and SRAM sections.
- LONG Align ; Alignment of this section (expressed as number of low bits ; to leave as 0). -1 if not defined.
- IF (Type == ROMX) || (Type == ROM0) ; Sections that can contain data.

BYTE Data[Size] ; Raw data of the section.

LONG NumberOfPatches ; Number of patches to apply.

; These types of sections may have patches

REPT NumberOfPatches

STRING	SourceFile	; Name of the source file (for printing error ; messages).
LONG	Line	; The line of the source file.
LONG	Offset	; Offset into the section where patch should ; be applied (in bytes).
BYTE	Туре	<pre>; 0 = BYTE patch. ; 1 = little endian WORD patch. ; 2 = little endian LONG patch.</pre>
LONG	RPNSize	; Size of the buffer with the RPN. ; expression.
BYTE	RPN[RPNSize]	; RPN expression. Definition below.

ENDR

ENDC

ENDR

RPN DATA

Expressions in the object file are stored as RPN. This is an expression of the form "2 5 +". This will first push the value "2" to the stack. Then "5". The "+" operator pops two arguments from the stack, adds them, and then pushes the result on the stack, effectively replacing the two top arguments with their sum. In the RGB format, RPN expressions are stored as BYTEs with some bytes being special prefixes for integers and symbols.

Value Meaning

```
$00
    + operator
$01
     - operator
$02
    * operator
$03
      / operator
$04
     % operator
$05
     unary -
$06
    operator
$07
    & operator
$08
     ^ operator
$09
    unary ~
$0A
     && comparison
$0B
     || comparison
$0C
    unary!
$0D
    == comparison
$0E != comparison
$0F > comparison
$10 < comparison
$11 >= comparison
$12
     <= comparison
$13
     << comparison
$14
     >> comparison
$15 BANK() function. A symbol ID follows.
$16 HRAMCheck. Check if the value is in HRAM, AND it with 0xFF.
$80
     LONG integer follows.
$81
     LONG Symbol ID follows.
```

SEE ALSO

```
rgbasm(1), rgblink(1), rgbds(7), gbz80(7)
```

HISTORY

rgbds was originally written by Carsten Sørensen as part of the ASMotor package, and was later packaged in RGBDS by Justin Lloyd. It is now maintained by a number of contributors at https://github.com/rednex/rgbds.